

 	<p><i>Rejitek high performance IB Series Box PCs offers a powerful, versatile, and cost-effective solution for dynamic industrial needs. Rejitek offers complete BOX PCs with a wide range of I/O interface and multiple expansions, allowing users to connect to different devices for comprehensive automation solution. The system design allows upgrading the memory, replacing the hard disk, or modifying the display size.</i></p> <p><b>Features</b></p> <ul style="list-style-type: none"> <li>» Fanless system with Intel® Core® i3/i5 Processor</li> <li>» Supports 6xCOM ports (COM1,2,5,6 RS-232/485/422;COM3,4 RS-232)</li> <li>» 2x Intel® Ethernet Controller I211</li> <li>» 9 V~36 V DC models available</li> <li>» Wide operating temperature: -20°C ~ 70°C</li> </ul>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

**Specification**

<b>Model Name</b>	IB-3720PF
<b>SBC Form Factor</b>	<b>CPU</b> Intel core i3 7100U / i5 7200U
	<b>Chipset</b> Intel SkyLake/Kaby Lake
	<b>System Memory</b> DDR4x1 SO-DIMM Slot, Max 16G
	<b>SSD/HDD</b> Support SSD/HDD, mSATA
	<b>Display Port</b> HDMI, VGA
	<b>Ethernet</b> 2x Intel® Ethernet Controller I211
<b>I/O Port</b>	<b>USB</b> 4xUSB2.0, 2xUSB3.0
	<b>COM Port</b> COM1,2,5,6 support RS-232/422/485 COM3,4 support RS-232
	<b>Audio</b> 1x Audio Line-out, 1xMic in
	<b>GPIO</b> 5-24V input, 8bit GPIO, 8bit GPO
	<b>Wireless</b> Option wifi module
	<b>System Controller</b> 1x Power Button 1x Power Input 1x Power LED 1x HDD LED 1x One-key recovery button
<b>Dimensions</b>	<b>Material</b> Aluminum alloy
	<b>Installation</b> Wall mount
	<b>Dimension</b> 197.7(L)x 232.5(W)x 66.5(H)mm
	<b>Weight</b> 3Kg
<b>Power</b> <b>Environment</b> <b>Operating System</b>	<b>Power Supply</b> 9~36V DC-Input
	<b>Operating Temperature</b> -20~70 °C
	<b>Humidity</b> Operating: 20% to 80% (No Condensation);
	<b>OS</b> Windows 10, Windows 7, windows 8, Linux