

**Features**

	<p>Rejitek provides a full range of ruggedized monitors with all-in-one PC and a rugged metal construction. The Industrial Panel PCs come in a wide range of sizes and features including touch screen technology, IC-rated protection and high brightness sunlight readable displays.</p> <ul style="list-style-type: none"> <li>● Optional can be haswell-U chipset with more powerful I3 / I5 / I7-U which is board-built with Intel HD graphics and audio decoding and the different capacity of memory is available, built-in MSTAT SSD.</li> <li>● Dual antenna WIFI, built-in speaker, 12V low voltage power supply</li> <li>● A range of I/O ports and support a variety of third-party peripherals. The standard ports include four RS-232 serial ports, four USB ports, Gigabit Ethernet interface RJ45 and a group of 3.5MM audio input port and a group of audio output port, a VGA and an HDMI video output port to be easy to increase the second monitor.</li> <li>● Industrial-grade LCD screen and capacitive touchscreen panel.</li> <li>● Waterproof, dustproof and explosion-proof: IP65 (front) IK08 (front).</li> <li>● Dense ventilation holes on the back, efficient heat dissipation.</li> <li>● Panel brightness(can choice 450nits,700nits,1000nits,1500nits,2000nits)</li> </ul>
--	--

**Specification**

<b>Product</b>	Model Name	IC-32170S		
<b>Construction</b>	Open Frame Monitors, Panel Mount, Chassis, Chassis Mount, Rack Mount.			
<b>Panel</b>	Size	17.0"	View Angle	L/R: 80/80; U/D: 80/80 (Typ.)(CR≥10)
	Max Resolution	1280x1024@60Hz/4:3 SXGA	Brightness	330 cd/m2
	Contrast Ratio	1000 :1	Colors	16.7M
<b>System</b>	Mother board	Intel Bay Trail-d chipset: Celeron J1900/1.99GHz Intel Core-U chipset : I3-U/ I5-U/ I7-U	WiFi	Built-in 802.11b / g / n wireless, external two 3DB antenna
	Memory	Optional 2GB,4GB,8GB	Ethernet	1 road onboard Realtek 8111e Gigabit
	Graphics	Onboard Intel HD graphics	Storage	SSD: 32G,64G,128G,256G,512G
	OS	Windows, Linux, Android, x86		HDD Optional
<b>I/O</b>	Video Output	1*VGA;1*HDMI	Serial Ports	4*RS232(standard)interfaces
	Ethernet	1 x RJ45 GbE LAN	USB Ports	4*USB TYPE-A
	Audio System	1*3.5mm Audio input; 1*3.5mm Audio output		
<b>Power</b>	Power Supply	External DC, Input Voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS		
<b>Environment</b>	Temperature	Operating: 0°C to 50°C; Storage: -20°C to 60°C		
	Humidity	Operating: 20% to 80% (No Condensation); Storage: 10% to 90% (Non-condensing)		
<b>Features</b>	User Controls	OSD Button: Menu, Up, Down, Select, Power		
<b>Certification</b>	EMC	FCC, CE		
<b>Options*</b>	Performance	IP65(Front)/IK08(Front)		
	TouchScreen	Projected Capacitive, Touch Points : 10 Points		
	Mounting Options	100mm or 75mm VESA Mounting, Open Bracket Mounting		
<b>Case Color</b>	Case/ Frame Color	Black		

**Ordering Information**

Model Name	Description
IC-32170S-33SX1A	Brightness 330 cd/m2
IC-32170S-A0SX1A	Brightness 1000 cd/m2
IC-32170S-A5SX1A	Brightness 1500 cd/m2