



Specification

Product	Model Name	IC-35215W		
Construction	VESA 100x100mm Mount.			
Panel	Size	21.5"	View Angle	L/R: 80/80; U/D: 80/80 (Typ.)(CR≥10)
	Max Resolution	1920x1080@60Hz/16:9 Full HD	Brightness	350 cd/m ²
	Contrast Ratio	1000 :1	Colors	16.7M
System	CPU	RK3399	WiFi	Built-in 802.11b / g / n wireless, external two 3DB antenna
	Memory	8GB		
	Graphics	Onboard Intel HD graphics		
	OS	ARM base		
I/O	Video Output	1*HDMI	USB Ports	2*USB TYPE
	Ethernet	1 * RJ45 GbE LAN	Port	1*RS232
	Audio System	1*3.5mm Audio input; 1*3.5mm Audio output		
Power	Power Supply	External DC, Input Voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS		
Environment	Temperature	Operating: 0°C to 50°C; Storage: -20°C to 60°C		
	Humidity	Operating: 20% to 80% (No Condensation); Storage: 10% to 90% (Non-condensing)		
Features	User Controls	OSD Button: Menu, Up, Down, Select, Power		
Certification	EMC	FCC, CE		
Options*	Performance	IP65(Front)/IK08(Front)		
	TouchScreen	Projected Capacitive, Touch Points : 10 Points		
	Mounting Options	100mm VESA Mounting		
Case Color	Case/ Frame Color	Black		

Ordering Information

Model Name	Description
IC-35215W-35FH1A	Brightness 350 cd/m ²
IC-35215W-A0FH1A	Brightness 1000 cd/m ²
IC-35215W-A5FH1A	Brightness 1500 cd/m ²