


Features

	<p>Rejitek provides a full range of ruggedized monitors with all-in-one PC and a rugged metal construction. The Industrial Panel PCs come in a wide range of sizes and features including touch screen technology, IC-rated protection and high brightness sunlight readable displays.</p> <ul style="list-style-type: none"> ● Optional can be haswell-U chipset with more powerful I3 / I5 / I7-U which is board-built with Intel HD graphics and audio decoding and the different capacity of memory is available, built-in MSTAT SSD. ● Dual antenna WIFI, built-in speaker, 12V low voltage power supply ● A range of I/O ports and support a variety of third-party peripherals. The standard ports include four RS-232 serial ports, four USB ports, Gigabit Ethernet interface RJ45 and a group of 3.5MM audio input port and a group of audio output port, a VGA and an HDMI video output port to be easy to increase the second monitor. ● Industrial-grade LCD screen and capacitive touchscreen panel. ● Waterproof, dustproof and explosion-proof: IP65 (front) IK08 (front). ● Dense ventilation holes on the back, efficient heat dissipation. ● Panel brightness(can choice 450nits,700nits,1000nits,1500nits,2000nits)
---	--

Specification

Product	Model Name	IC-32238W		
Construction	Open Frame Monitors, Panel Mount, Chassis, Chassis Mount, Rack Mount.			
Panel	Size	23.8"	View Angle	L/R: 80/80; U/D: 80/80 (Typ.)(CR≥10)
	Max Resolution	1920x1080@60Hz/16:9 Full HD	Brightness	350 cd/m2
	Contrast Ratio	1000 :1	Colors	16.7M
System	Mother board	Intel Bay Trail-d chipset: Celeron J1900/1.99GHz Intel Core-U chipset : I3-U/ I5-U/ I7-U	WiFi	Built-in 802.11b / g / n wireless, external two 3DB antenna
	Memory	Optional 2GB,4GB,8GB	Ethernet	1 road onboard Realtek 8111e Gigabit
	Graphics	Onboard Intel HD graphics	Storage	SSD: 32G,64G,128G,256G,512G
	OS	Windows, Linux, Android, x86		HDD Optional
I/O	Video Output	1*VGA;1*HDMI	Serial Ports	4*RS232(standard)interfaces
	Ethernet	1 x RJ45 GbE LAN	USB Ports	4*USB TYPE-A
	Audio System	1*3.5mm Audio input; 1*3.5mm Audio output		
Power	Power Supply	External DC, Input Voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS		
Environment	Temperature	Operating: 0°C to 50°C; Storage: -20°C to 60°C		
	Humidity	Operating: 20% to 80% (No Condensation); Storage: 10% to 90% (Non-condensing)		
Features	User Controls	OSD Button: Menu, Up, Down, Select, Power		
Certification	EMC	FCC, CE		
Options*	Performance	IP65(Front)/IK08(Front)		
	TouchScreen	Projected Capacitive, Touch Points : 10 Points		
	Mounting Options	100mm or 75mm VESA Mounting, Open Bracket Mounting		
Case Color	Case/ Frame Color	Black		

Ordering Information

Model Name	Description
IC-32238W-35FH1A	Brightness 350 cd/m2
IC-32238W-A0FH1A	Brightness 1000 cd/m2
IC-32238W-A5FH1A	Brightness 1500 cd/m2