

Features



Rejitek provides a full range of ruggedized monitors with brilliant displays and a rugged metal construction. The displays come in a wide range of sizes and features including touch screen technology, IP-rated protection, military-grade standards, and high brightness sunlight readable displays.

- Industrial-grade LCD screen
- Options for Advanced Optical Bonding.
- Dense ventilation holes on the back, efficient heat dissipation.
- Uses the most advanced LED backlight technology.

Product Customizable/Display Ports

We provide a wide range of customization options to meet your requirements.

- Size or structure
- choice 400nits,700nits,1000nits,1500nits,2000nits)
- Display ports (can choice VGA,DVI,HDMI,DP or more)

Specification

| | | |
|----------------------|-------------------------|---|
| Product | Model Name | IM-32084W Series |
| Construction | Type | Panel Mount Monitor |
| Panel | Size | 8.4" |
| | Max Resolution | 800x600@60Hz/4:3 SVGA |
| | View Angle(From Center) | L/R: 80/80; U/D: 80/60 (Typ.)(CR≥10) |
| | Brightness | 250cd/ m ² ,400cd/ m ² |
| | Response Time | ≤ 35ms |
| I/O | Display Ports | VGA, HDMI, (Option: Composite) |
| Power | Power Supply | External DC, Input Voltage DC: 12V; INPUT POWER CONNECTOR SPECIFICATIONS |
| | | Options: DC 9-36V, DC 24V |
| Environment | Temperature | Operating: 0°C to 50°C; Storage: -20°C to 60°C |
| | Humidity | Operating: 20% to 80% (No Condensation); Storage: 10% to 90% (Non-condensing) |
| | Features | User Controls OSD Buttons: Menu, Up, Down, Select, Power; (Options: flay cable, RJ45 cable) |
| Certification | EMC | FCC, CE |
| Options | Touchscreen | PCAP: Projected Capacitive Touchscreen, Touch Points : 10 Points Resistive Touchscreen |
| | Performance | IP65(Front) |
| | Mounting Options | 100mm or 75mm VESA Mounting, Open Bracket Mounting |
| Case Color | Case/ Frame Color | Black |

Ordering Information

| Model Name | Description |
|------------------|----------------------------------|
| IM-32084S-25SV5A | Brightness 250 cd/m ² |
| IM-32084S-40SV5A | Brightness 400 cd/m ² |

Options: I/O Connectors

Display Ports I/O



HDMI



DisplayPort




VGA



DVI

Power Ports I/O



DC 9-36V
phoenix connector



DC 12V
Power connector



AC 110/220V
Power connector

Model Name

IM-33650W-B5FH1A

