

## Features



Rejitek provides a full range of ruggedized monitors with brilliant displays and a rugged metal construction. The displays come in a wide range of sizes and features including touch screen technology, IP-rated protection, military-grade standards, and high brightness sunlight readable displays.

- Industrial-grade LCD screen
- Waterproof, dustproof and explosion-proof: IP65 front
- Dense ventilation holes on the back, efficient heat dissipation.
- Uses the most advanced LED backlight technology.
- High Brightness: 1000nits
- Displays I/O: HDMI+VGA
- VESA 100x100mm
- Options:
  - Optical Bonding
  - Conformal Coating
  - VR Knob
  - Wide Voltage:9-36VDC Terminal Block

## Specification

<b>Product</b>	<b>Model Name</b>	<b>IM-32270W</b>
<b>Construction</b>	Type	Panel Mount Monitor
<b>Panel</b>	Size	27.0"
	Max Resolution	1920x1080@60Hz/16:9 Full HD
	View Angle(From Center)	L/R: 85/85; U/D: 80/80 (Typ.)(CR≥10)
	Brightness	300cd/ m <sup>2</sup> ~1500cd/m <sup>2</sup>
	Response Time	≤ 15ms
<b>I/O</b>	Display Ports	VGA, HDMI (option DVI, DP)
<b>Power</b>	Power Supply	External DC, Input Voltage DC: 12V PSE AC Adaptor
<b>Environment</b>	Temperature	Operating: 0°C to 60°C; (option Wide Temp: -20C~+70C) Storage: -20°C to 60°C
	Humidity	Operating: 20% to 80% (No Condensation); Storage: 10% to 90% (Non-condensing)
<b>Certification</b>	EMC	FCC, CE
<b>Features</b>	User Controls	OSD Buttons: Menu, Up, Down, Select, Power
	Mounting 1	VESA 100mm x 100mm
	Mounting 2	Panel Mount Kit
<b>Options</b>	Bonding	Optical Bonding
	Touchscreen	PCAP or RTP
	Performance	IP65 Front
	Wide Voltage	9-36VDC Terminal Block
	Dimming	VR Knob (0-100%)
<b>Case Color</b>	Case/ Frame Color	Black

## Ordering Information

Model Name	Description
<b>IM-32270W-30FH1A</b>	Brightness 300 cd/m <sup>2</sup>
<b>IM-32270W-A0FH1A</b>	Brightness 1000 cd/m <sup>2</sup>
<b>IM-32270W-A5FH1A</b>	Brightness 1500 cd/m <sup>2</sup>