

Features



Rejitek provides a full range of ruggedized monitors with brilliant displays and a rugged metal construction. The displays come in a wide range of sizes and features including touch screen technology, IP-rated protection, military-grade standards, and high brightness sunlight readable displays.

- Industrial-grade LCD screen
- Waterproof, dustproof and explosion-proof: IP65 front
- Dense ventilation holes on the back, efficient heat dissipation.
- Uses the most advanced LED backlight technology.
- High Brightness: 1000nits~1500nits
- Displays I/O: HDMI+VGA
- VESA 100x100mm
- Options:
 - Touchscreen: PCAP or RTP
 - Optical Bonding
 - Conformal Coating
 - VR Knob
 - Wide Voltage:9-36VDC Terminal Block

Specification

| | | |
|----------------------|-------------------------|--|
| Product | Model Name | IM-33270W |
| Construction | Type | Chassis Monitor |
| Panel | Size | 27.0" |
| | Max Resolution | 1920x1080@60Hz/16:9 Full HD |
| | View Angle(From Center) | L/R: 85/85; U/D: 80/80 (Typ.)(CR≥10) |
| | Brightness | 300cd/ m ² ~ 1500cd/ m ² |
| | Response Time | ≤ 15ms |
| I/O | Display Ports | VGA, HDMI(Option DVI, DP) |
| Power | Power Supply | External DC, Input Voltage DC: 12V PSE AC Adaptor |
| Environment | Temperature | Operating: 0°C to 60°C; (Option Wide temp:-20~+70C) Storage: -20°C to 60°C |
| | Humidity | Operating: 20% to 80% (No Condensation); Storage: 10% to 90% (Non-condensing) |
| Certification | EMC | FCC, CE |
| Features | User Controls | OSD Buttons: Menu, Up, Down, Select, Power |
| | Performance | IP65 Front(Option) |
| | Mounting 1 | VESA 100mm x 100mm |
| Options | Bonding | Optical Bonding |
| | Wide Voltage | 9-36VDC Terminal Block |
| | Dimming | VR Knob (0-100%) |
| | Touchscreen | PCAP or RTP |
| Case Color | Case/ Frame Color | Black |

Ordering Information

| Model Name | Description |
|------------------|-----------------------|
| IM-33270W-30FH1A | Brightness 300 cd/m2 |
| IM-33270W-A0FH1A | Brightness 1000 cd/m2 |
| IM-33270W-A5FH1A | Brightness 1500 cd/m2 |