Features



Rejitek range of Industrial Displays have been designed and built to withstand harsh environments. Our range of Waterproof Displays are IP66 rated for peace of mind when water or dust are present in your working environment, a full wash-down of this product is also no problem.

Features

- Enhanced Reliability & Performance
- 6-Sides Fully IP66 Sealed
- VGA and HDMI Inputs
- Resistive / Surface Capacitive Touch Options
- Ultra-Wide Temperature Range Option
- Mild Steel or Stainless Steel Housing
- **VESA Standard Interface Mounting**
- Options:
 - PCT/RT Touchscreen
 - DC 9-36V
 - Wide Temperature

Specification

Product	Model Name	IM-36213S
Construction	Туре	IP66 Stainless Steel Monitor
Panel	Size	21.3" 4:3
	Max Resolution	2048x1536@60Hz/4:3/QXGA
	Display Area	433.15mm (H) / 324.86mm(V)
	View Angle(From Center)	L/R: 89/89; U/D: 89/89 (Typ.)(CR≥10)
	Brightness	800 cd/m2
	Contrast Ratio	1200:1
1/0	Display Ports	VGA, HDMI(Optional)
	Audio System	N/A
Power	Power Supply	Input Voltage DC: 12V
Environment	Temperature	Operating: 0°C to 60°C
		Storage: -20°C to 60°C
	Humidity	Operating: 10% to 90% (No Condensation)
		Storage: 10% to 90% (Non-condensing)
Features	User Controls	OSD-Multi Language
Certification	EMC	FCC, CE
Options*	Performance	IP66
	Mounting Options	200mm or 100mm VESA Mounting, Open Bracket Mounting
Case Color	Case/ Frame Color	Silver

Ordering Information

Model Name	Description
IM-36213S-80QX1A	Brightness 800 cd/m2