

Features



Rejitek range of Industrial Displays have been designed and built to withstand harsh environments. Our range of Waterproof Displays are IP66 rated for peace of mind when water or dust are present in your working environment, a full wash-down of this product is also no problem.

Features

- Enhanced Reliability & Performance
- 6-Sides Fully IP66 Sealed
- VGA and HDMI Inputs
- Resistive / Surface Capacitive Touch Options
- Ultra-Wide Temperature Range Option
- Mild Steel or Stainless Steel Housing
- VESA Standard Interface Mounting
- Options:
 - PCT/RT Touchscreen
 - DC 9-36V
 - Wide Temperature

Specification

Product	Model Name	IM-36490W
Construction	Type	IP66 Stainless Steel Monitor
Panel	Size	49.0"
	Max Resolution	1920x1080@60Hz/16:9/FULL HD
	View Angle(From Center)	L/R: 85/85; U/D: 80/80 (Typ.)(CR≥ 10)
	Brightness	350~2500 cd/m ²
	Contrast Ratio	1000 :1
I/O	Display Ports	VGA, HDMI
	Audio System	Option
Power	Power Supply	Input Voltage DC: 12V (Options DC36-9V/AC110-230V)
Environment	Temperature	Operating: 0°C to 60°C Storage: -20°C to 60°C
	Humidity	Operating: 10% to 90% (No Condensation) Storage: 10% to 90% (Non-condensing)
Features	User Controls	OSD-Multi Language
Certification	EMC	FCC, CE
Options*	Performance	IP66
	Mounting Options	100mm or 50mm VESA Mounting, Open Bracket Mounting
	Touchscreen	PCT/RT Touchscre
	Wide Temperature	-20-70 °C
Case Color	Case/ Frame Color	Silver

Ordering Information

Model Name	Description
IM-36490W-35FH1A	Brightness 35cd/m ²
IM-36490W-A0FH1A	Brightness 1000 cd/m ²
IM-36490W-A5FH1A	Brightness 1500 cd/m ²
IM-36490W-B5FH1A	Brightness 2500 cd/m ²