Features



Rejitek provides a full range of ruggedized monitors with brilliant displays and a rugged metal construction. The displays come in a wide range of sizes and features including touch screen technology, IP-rated protection, military-grade standards, and high brightness sunlight readable displays.

- Industrial-grade LCD screen
- Options for PCAP or Resistive Touchscreen .
- Options for Waterproof, dustproof and explosion-proof: IP65 front
- Options for Advanced Optical Bonding.
- Dense ventilation holes on the back, efficient heat dissipation.
- Uses the most advanced LED backlight technology.

Product Customizable/Display Ports

We provide a wide range of customization options to meet your requirements.

- Size or structure
- Options: Glass covers surface treatment AG, AF, AR.
- Panel brightness(can choice 400nits, 700nits, 1000nits)
- Display ports (can choice VGA,DVI,HDMI,DP or more)

Specification

Product	Model Name	IM-32070W-40WV5A
Construction	Туре	Panel Mount Monitor
Panel	Size	7"
	Max Resolution	800x480 16:9
	View Angle(From Center)	L/R: 65/65; U/D: 65/65 (Typ.)(CR≥10)
	Brightness	400 cd/ m ²
	Response Time	≤ 35ms
I/O	Display Ports	Composite
Power	Power Supply	DC 9-36V Phoenix connector
Environment	Temperature	Operating: 0°C to 60°C;
		Storage: -20°C to 60°C
	Humidity	Operating: 20% to 80% (No Condensation);
		Storage: 10% to 90% (Non-condensing)
Features	User Controls	OSD Buttons: Menu, Up, Down, Select, Power; (Options: flay cable, RJ45 cable)
Certification	EMC	FCC, CE
Options	Touchscreen	PCAP: Projected Capacitive Touchscreen, Touch Points : 10 Points
		Resistive Touchscreen
	Performance	IP65(Front)
	Mounting Options	100mm or 75mm VESA Mounting, Open Bracket Mounting
Case Color	Case/ Frame Color	Black

Ordering Information

Model Name	Description
IM-32070W-40WV5A	Brightness 400cd/m2

Options: I/O Connectors

Display Ports I/O



Power Ports I/O



DC 9-36V phoenix connector



Power connector



AC 110/220V Power connector

Model Name

IM-33650W-B5FH1A

